

DS-609-50T/-30T/-120T 皮面压花机

PERFORATING & EMBOSING MACHINE

主要特点: FEATURES

01
上模板通过加热, 软化皮料。
The upper molding plate softens leather material by heating.

02
加热温度、压合时间可设定, 并根据需要调整。
Heating and pressing time can be set and adjusted as required.

03
采用外拉式工作台, 操作方便安全。
Convenient and safe draw-out working table is adopted.

04
采用双联油缸增压机构, 增压速度快, 压力大, 耗能低。
Duplex oil cylinder booster mechanism is adopted, which has a high pressurizing speed, large pressure and low energy consumption.

主要参数: MAIN TECHNICAL PARAMETERS

电机功率	Motor Power	1.5kW
加热功率	Heating Power	3kW
总功率	General Power	4.5kW
电源电压	Power Supply Voltage	380V
供电相数	Power Supply Phase	3-Phase
频率	Frequency	50Hz
最大工件面积	Max. Working Area	300 × 315mm (30T/50T)
		350 × 360mm (120T)
最大工作压力	Max. Working Pressure	30/50/120Tons
机器净重	Machine Net Weight	565kg
包装重量	Package Weight	640kg
外形尺寸	External Dimensions(LWH)	96 × 68 × 158(cm)
外包装尺寸	Package Dimensions(LWH)	106 × 78 × 170(cm)

DS-609

DASHUN

DASHUN SHOE MACHINERY

DS-609-50T/-30T/-120T 皮面压花机

Perforating & Embossing Machine
本机适用于压制皮面各种花纹, 冲孔。
Used to emboss different patterns or punch on leather surface

